

# Table of Cont

1	MACHINE LANGUAGE COMPILER (MASD).....	
1.1	Generalities on ML (Machine Language) .....	
1.2	Launching Masd.....	<b>Error! B</b>
1.3	Generalities on Masd Syntax .....	
1.4	Links .....	<b>Error! B</b>
1.5	Using labels .....	
1.6	Using constants .....	
1.7	Expressions .....	
1.8	Skips.....	
1.9	SATURN instructions syntax.....	
1.9.1	Assigning 0 to a register .....	
1.9.2	Loading a value in A or C.....	
1.9.3	Loading a register value into another register.....	
1.9.4	Exchange between two registers .....	
1.9.5	Addition .....	
1.9.6	Subtraction.....	
1.9.7	Increment and decrement.....	
1.9.8	Right nibbles shifting (divide by 16).....	
1.9.9	Left nibbles shifting (multiply by 16).....	
1.9.10	Right bit shifting (divide by 2).....	
1.9.11	Right circular nibble shifting.....	
1.9.12	Left circular nibble shifting.....	
1.9.13	Logical AND .....	
1.9.14	Logical OR .....	
1.9.15	Logical NOT.....	
1.9.16	Mathematical NOT .....	
1.9.17	Loading value into a R Register .....	
1.9.18	Loading value into A or C from a R register .....	
1.9.19	Exchange between A or C and a R register .....	
1.9.20	Memory write (POKE).....	
1.9.21	Memory read (PEEK) .....	
1.9.22	D0 and D1 modifications .....	
a)	Loading D0 and D1 .....	
b)	Exchanges between A or C and D0 or D1 .....	
◆	Loading A or C, field A, into D0 or D1 .....	
◆	Loading the four low nibbles of A or C into D0 .....	
◆	Exchanging A or C, field A, and D0 or D1. ....	
◆	Exchanging the 4 first nibbles of A or C and D0 .....	
c)	Increment and decrement of D0 and D1 .....	

ing registers tests .....	11
y and inequality tests .....	11
and greater tests .....	11
tests .....	11
ing with some bits of A or C register .....	11
ions on PC .....	11
ing with the Hardware Status Register .....	12
ing with P .....	12
nstructions .....	12
ages between C and RSTK .....	12
output instructions .....	12
or control instructions .....	13
.....	<b>14</b>
TO ASSEMBLY LANGUAGE .....	15
<i>m</i> .....	15
<i>sembly language (asm) ?</i> .....	15
<i>i processor</i> .....	15
ilities .....	15
ing and saving registers .....	15
ler .....	16
egister .....	16
stack .....	16
y pointers .....	16
y .....	16
s .....	16
y accesses .....	17
<i>nd stopping a Program</i> .....	17
<i>ith the RPL stack</i> .....	17
<i>truction set</i> .....	18
.....	<b>27</b>

# 1 Machine Language Compiler

## 1.1 Before you start

This section will talk about the MASD syntax as used with the HPTools v3.0.

There are some differences between the MASD syntax and the one used with the HPTools.

The main limitations are the expressions that are compiled (the MK v2.0) and operations can't be performed on two exte

## 1.2 Generalities on ML (Machine Language)

As the Saturn processor directly executes ML, the operation what a ML program is doing.

On the HP 48 calculator, user data are stored in the same. When there is a bug in a ML program, you have best chance very careful when programming in ML.

ML is a processor dependent language, so what you will learn not be useful on other processor. On the other hand, the programs will acquire are not dependent of the hardware and then will

## 1.3 Generalities on Masd Syntax

Masd expects a character string (called source) on the top of a carriage return and an arobas @.

Masd is case sensitive, so be careful, as « boucl e » ; different labels.

Separation characters are those with an ASCII number spaces, tabs, line feed and carriage return.

Some instructions need a parameter, called field. Separation instruction and the field, are spaces, tabs, and points. Then instead of A+B A.

Comments can be placed everywhere between two instructions ; and finish at the end of the current line.

## 1.4 Using labels

A label is a marker in the program. The principal use of labels destinations.

A label is a set of less than 128 characters different from spaces. A label begins with a star '\*' and ends with a separation character. \*Bi gLoop is the BigLoop label declaration.

Be careful about upper and lower cases!

if labels can be used:

It is a label that can be used everywhere in the project, like global labels in Pascal or C.

It is a label that is only accessible in a local section like local variables in

It starts at the beginning of a source, after a global label, after a link (see

It finishes at the end of a source, before a link, before a global label.

It is identified by a '\$' as the first character.

It is a label that exists only in the link where it is declared, like a private label in Pascal.

It is identified by a '\_' as the first character.

In general, using less global labels is better because a global label is longer to type because it gives a better program structure. A good habit is to use global labels for the program in subroutines, and to use local labels inside these

## Constants

Labels can be used to define constants. It is useful to identify a memory address by a name, instead of typing the address itself.

Instead of typing `D1=80100` every time it is needed, it is better to declare `Result 80100` at the beginning of the project and then to type `Result` when needed.

Labels can be used for:

`name Expression` or

`name Expression` or

`name Expression`

`name CstValue` or `EQU name CstValue`

where `name` is a hexadecimal number. A decimal number can be typed with a leading #

is the same as `DC Foo #16`

A constant cannot be given the same name as a declared label.

The name of a constant follows the same rules as the name of a label.

There is a 'programming register' called CP (Constant Pointer) which helps to store constants. CP is defined by:

`PE=Expression`

where `PE` is on 5 nibbles, its initial value is 80100.

DCCP *Increment ConstantName*

declares a constant with the current CP value and then increments it by *Increment*.

Note: *Increment* is a hexadecimal value, to use a decimal value use *D*.

For example, if CP equals to \$10

DCCP 5 Foo

defines a Foo constant with a value of \$10 and then changes it to \$15.

Several constants can be defined, starting from CP.

: *Inc CstName0 CstName1 ... CstNameN-1 :*

defines *N* constants *CstName<sub>x</sub>* with a value of  $CP+x*Inc$ .  
The value of *CstName<sub>0</sub>* is *CP* and the value of *CstName<sub>N-1</sub>* is  $CP+(N-1)*Inc$ .

Warning: By default, *Inc* is an hexadecimal number. Meta uses *D* for decimal.

## 1.6 Expressions

An expression is a mathematical operation that is calculated.

Terms of this operation are hexadecimal or decimal values, separated by spaces.

An expression stops on a separation character.

DCCP 5 @Data

...

D1=(5)@Data+\$10/#2 DO=(5)\$5+DUP

are correct expressions.

Notes:

- A hexadecimal value must begin with a \$ and a decimal value with D.
- There are no priorities (precedences) in operations. \$1+\$2\*3 requires parentheses to set precedences.
- You can't use more than three levels of parenthesis.
- Calculations are done on 32 bits.

## 1.7 Skips

Skips are a first step from ML to a third generation language. They provide another way to write SATURN instructions.

The basement of Skips is the Block structure.

A block is enclosed in { and }, and can be inside another block.

The following instructions deal with blocks.

SKIPS instructions	Equivalents
SKI P { ... }	GOTO . S ... *. S
SKI PL { ... }	GOTOL . S ... *. S
SKI PC { ... }	GOC . S ... *. S
SKC { ... }	GOC . S ... *. S
SKI PNC { ... }	GONC . S ... *. S
SKNC { ... }	GONC . S ... *. S

Meta Kernel

Appendixes

Test GOYES . S ... *. S
Test GOYES . S ... *. S
/Test GOYES . S ... *. S
GOSUB . S ... *. S
GOSUBL . S ... *. S
Defines a block (generates no code)
\$/O2A2C GOI N5 *. S ... *. S (to create a character string)
\$/O2DCC GOI N5 *. S ... *. S (to create a code object)
.. \$/PROLOG GOI N5 . S ... *. S (to create a 'prolog - length' object)

posite of Test. For example if Test is ?A<C. A, /Test is ?A>=C. A. instructions dealing with the hardware register (?HST=0, ?MP=0, =0 and ?SB=0) cannot be inverted.

re defined, special instructions can be used in them. These instructions and UP allow to jump to the end or to the beginning of a block.

ctions	are equivalent to
EXI T	*. Begi nni ng GOTO. End GOC. End GONC. End ?A=0. A .. End GOTO. Begi nni ng GOC. Begi nni ng GONC. Begi nni ng
UP	?A=0. A .. Begi nni ng *. End

ake confusion between EXIT and UP instructions, which are GOTOS, UP after a test, which are GOYES's.

can jump to the beginning or to the end of an upper-level block by number of blocks to exit, after the UP or EXIT instructions.

ctions	Are equivalent to
2	*. Beg3 *. Beg2 *. Beg1
3	GOTO. Beg2 GOTO. Beg3
I T1	GOTO. End1
I T3	GOTO. End3 *. End1 *. End2 *. End3

; equivalent to EXIT, and UP1 is equivalent to UP.

LSE, SKEC or SKENC instructions, two blocks create an IFNOT-structure.

Are equivalent to	Or in high-level language
?A=0. A GOYES. Beg2 *. Beg1	I F NOT A=0 THEN BEGI N



or LA(x) Exp load the result of an expression into C or A, using x

5) @Buffer+DataOffset

### Register value into another register

*=Reg2.f*

}. X

### Between two registers

*Reg2EX.f*

}. X. W

*=Reg1+Reg2.f* or *Reg1+Reg2.f*

}. +A. A or C+A. A

and *Reg2* are same, this cause to multiply the register by two.

*=Reg1-Reg2.f* or *Reg1-Reg2.f*

}. -B. A or C-B. A

following instructions are also available:

*B=C-B.f* *C=A-C.f* *D=C-D.f*

### And decrement

*Reg+Cst.f* or *Reg+Cst.f* *Reg=Reg-Cst.f* or *Reg-Cst.f*

}. +10. A or A+10. A *A=A-10. A* or *A-10. A*

Saturn processor is not able to add a constant greater than 16 to a register, if *cst* is greater than 16, Masd will generate as many instructions as

if adding constants to a register is very useful, big constants should be avoided, because this will slow down execution, and generate a big program.

Using a constant greater than 1 to a P, WP, XS or S field is a bugged instruction (problem with carry propagation). Use these instructions with

adding a constant greater than 16 to a register, the carry should not be

### Right shifting (divide by 16)

*R.f*

}. W

### Left shifting (multiply by 16)

*L.f*

}. W

**1.8.10 Right bit shifting (divide by 2)**

Syntax: *RegSRB.f*

Example: ASRB. W

**1.8.11 Right circular nibble shifting**

Syntax: *RegSRC.f*

Example: ASRC. W

**1.8.12 Left circular nibble shifting**

Syntax: *RegSLC.f*

Example: ASLC. W

**1.8.13 Logical AND**

Syntax: *Reg1=Reg1&Reg2.f* or *Reg1&Reg2.f*

Example: C=C&B. A or C&B. A

**1.8.14 Logical OR**

Syntax: *Reg1=Reg1!Reg2.f* or *Reg1!Reg2.f*

Example: C=C! B. A or C! B. A

**1.8.15 Logical NOT**

Syntax: *Reg1=-Reg1-1.f*

Example: C=-C-1. A

**1.8.16 Mathematical NOT**

Syntax: *Reg1=-Reg1.f*

Example: C=-C. A

**1.8.17 Loading value into a R Register**

Syntax: *RReg=Reg.f*

Example: RO=A. W

Note: *Reg* can only be A or C.

**1.8.18 Loading value into A or C from a R register**

Syntax: *Reg=RReg.f*

Example: A=R1. X

Note: *Reg* can only be A or C.

**1.8.19 Exchange between A or C and a R register**

Syntax: *RegRRegEX.f*

Example: AR1EX. X

Note: *Reg* can only be A or C.

## **e (POKE)**

Instructions write the value of A or C at the address pointed to by D0 or D1.

*Reg.f* or *Data=Reg.x*  
:1=C. A or DATO=A. 10  
: only be A or C.

## **I (PEEK)**

Instructions load into A or C the data pointed to by D0 or D1.

*Data.f* or *Reg=Data.x*  
:A1. A or A=DATO. 10  
: only be A or C.

## **Modifications**

### **Load D1**

*=hh* or *DReg=hhh* or *DReg=hhhh* or  
*=(2)Exp* or *DReg=(4)Exp* or *DReg=(5)Exp*  
:FF D0=12345 D1=(5) toto+\$5

### **Store A or C into D0 or D1**

Store C, field A, into D0 or D1

*=Reg*  
:A  
: only be A or C.

Store four low nibbles of A or C into D0 or D1

*=RegS*  
:AS  
: only be A or C.

Store A or C, field A, and D0 or D1.

*RegEX*  
:EX  
: only be A or C.

Store the 4 first nibbles of A or C and D0 or D1

*RegXS*  
:XS  
: only be A or C.

### **Increment or decrement of D0 and D1**

*=DReg+Cst* or *DReg+Cst*  
*=DReg-Cst* or *DReg-Cst*  
:D0+12 D1-50

Note 1: The Saturn processor is not able to add a constant to a register but if *cst* is greater than 16, Masd will generate the code needed.

Note 2: Even if adding constants to a register is very useful, it is avoided because this will slow down execution, and generate code.

Note 3: After adding a constant greater than 16, the carry flag is set.

### 1.8.23 Working registers tests

Notes:

- A test is always followed by RTNYES, GOYES, SKIP, GOTOL, GOVLNG, GOSUB, GOSUBL or GOSBVL.
- RTY is the same as RTNYES.
- An arrow (→) may be followed by a label name, then replaced by a skip block, which is equivalent to the inverse: SKIPYES, to reproduce a IF-THEN structure. Example: ?A=C. A { }.
- SKIP YES may be omitted if followed by a skip block ({}).
- If the test is followed by a GOTO, GOTOL, GOVLNG, GOSUB, Masd compiles the inverse of the test, to reproduce a GOTO. Example: ?A=C. A GOTO B is the same as ?A#C. A { }.
- GOTO, GOTOL, GOVLNG, GOSUB, GOSUBL, GOSBVL or a HST test.
- A label name must follow a GOYES, GOTO, GOTOL, GOVLNG, GOSBVL.

#### a) Equality and inequality tests

Syntax: ?Reg1=Reg2.f      ?Reg1#Reg2.f

Example: ?A=C. B      ?C#D. A

Note: The HP inequality character may be used.

#### b) Lower and greater tests

Syntax: ?Reg1<Reg2.f      ?Reg1<=Reg2.f

Example: ?A<C. B      ?C>=D. A

Note: The HP lower or equal and greater or equal characters.

#### c) Nullity tests

Syntax: ?Reg=0.f      ?Reg#0.f

Example: ?A=0. B      ?C#0. XS

Note: The HP inequality character may be used.

### 1.8.24 Working with some bits of A or C register

RegBIT=v.a      ?RegBIT=v.a where Reg is A or C, v is 0 or 1, a is the bit number.

Examples: ABI T=0. 5, ?CBI T=1. 3 GOYES TOTO

### 1.8.25 Operations on PC

A=PC    C=PC    PC=A    PC=C    APCEX    CPCEX

Meta Kernel

Appendixes

## the Hardware Status Register

SR=0 MP=0 HST=*a*  
=0 ?SR=0 ?MP=0 ?HST=*a*

## P

P=P-1 P-1

. *a* CPEX. *a*  
+P+1

## itions

*l*  
*el* or GOLONG *l* *abel*  
*t* *Cst* is an hexadecimal number.  
*abel* *label* is a constant, or a label in absolute mode  
COMMAND" *Command* is an entry in the STARTEXT table.  
*el*  
*bel*  
*t* *Cst* is a hexadecimal number.  
*abel* *label* is a constant, or a label in absolute mode.  
COMMAND" *COMMAND* is an entry in the STARTEXT table.

*l*  
*el* same as SKI PNC { GOTO *l* *abel* }  
*bel* same as SKI PC { GOTO *l* *abel* }

M RTNCC RTNSC RTI  
C  
RTY after a test.

## etween C and RSTK

RSTK=C instructions allow to push to or pop data from the Saturn

## t instructions

T=C, A=I N and C=I N  
and C=I N instructions are bugged (they only work on even addresses).  
2 and C=I N2, which are ROM calls to A=I N and C=I N instructions.  
beginning of ROM is not usable (because it is recovered by RAM), use  
C=I N3, which are calls to A=I N and C=I N instructions in the **Meta**  
C=I N is a ROM call that does OUT=C C=I N.

Note 4: OUT=C=I N3 is the same, but in the **Meta Kernel** ROM is recovered).

### 1.8.31 Processor control instructions

Working mode modification

SETDEC SETHEX

other instructions

UNCNGF CONFIG RESET C=I D

SHUTDN INTON INTOFF RSI

SREQ?

BUSCB BUSCC BUSCD

# Appendixes

# 1 Introduction to assembly language

## 1.1 Introduction

Our purpose here is to help you translate an algorithm in S using Masd. You are supposed to already know the program language.

If you want to learn how to program, there are several books 'The Art of Programming'.

We will try to give you the basis to build little programs. With experience, look at other people's programs, and read more on the subject.

Many informations here are taken from the excellent French book 'de la HP48' by Paul Courbis (Angkor).

## 1.2 What is assembly language (asm) ?

Asm is the only language directly readable by the microprocessor. It is the fastest and the most powerful language. Each processor is composed of binary numbers interpreted by the processor giving instructions to be processed.

To make it easily readable by humans, each group of numbers is mnemonic. Assemblers (like Masd) translate these mnemonics into the processor can execute. They sometimes add macros to ease the programmer's work.

## 1.3 The Saturn processor

### 1.3.1 Generalities

SATURN is the name of a processor made by NEC. It is a 16-bit processor (it can process 4 bits at each clock tick), with 5 64-bit saving registers, 2 20-bit memory pointers, an internal software flags, 4 hardware flags, 1 field register, 1 output register and 1 20-bit program counter.

A bit is a binary digit, it can take only two values 0 or 1.

A nibble is a 4-bit value, from 0 to 15.

### 1.3.2 Working and saving registers


These registers are 64-bit (16-nibble) registers divided into 16 nibbles. A field is a part of a register; a group of nibbles. Two fields have different lengths.

In a Saturn register, there are six fixed fields and two variable fields:

15	14	13	12	11	10	9	8	7	6	5	4	
(With P=9)						P						

Meta Kernel

Appendixes



Writing with the A field only affects the 20 lowest bits of the register.  
 WP means register C, field B.

Register which indicates the WP field length, the P field location, and the nibble for the instructions LA and LC.

**Flags**  
 Register is a 16-bit register, composed of 16 flags, which can be only 0 or 1. Similar to RPL flags (CF, SF...).

Stack is a set of eight 20-bit registers. Only one of them is accessible (ie RPL stack).

When a routine is called (with GOSUB), the return address (just after the GOSUB) is pushed onto this stack. And when a RTN is encountered, the Saturn pops this from the stack and jumps to it.

Registers are only eight levels, building large programs with a lot of subroutine calls can overload the return stack.

able to push a value with RSTK=C and to pop a value with C=RSTK.

### Registers

Memory pointers D0, D1 and PC are 20-bit registers, which contains

are used to access memory. You can load any address in them and then

Program Counter, it holds the address of the next instruction to be executed. It is modified at every jump (GOTO, GOSUB...), or directly with instructions like JUMP.

When using pointers, let's see how memory is seen through HP asm.

Memory can be compared to a ring of cells. Each cell contains one nibble. They are numbered from 0 to 524287 (20 bits). It is a ring, so the cell 524287 is followed by cell 0. The number of a cell is called its address.

Each register that contains an address. On HP48, a pointer is 20 bits (5 nibbles). Therefore we can access any memory cell with one pointer (Whereas on HP41C we need two pointers).

**c) Memory accesses**

On the HP48, memory inputs and outputs are made through D0 and D1 indicating which cell will be accessed.

It is possible to access more than one cell at one time, as 12 nibbles (3 bytes) can be loaded.

A=DATO A reads 5 nibbles at the address pointed by D0, the 5 lowest nibbles of A (Aa).

DAT1=C 12 writes 12 nibbles at the address pointed by D1, the 12 lowest nibbles of C (nibbles 0 to 11).

Note that the Saturn processor inverses the order of the nibbles. If D0 contains 84571 and D1 contains 80200, DAT1=C A will contain 14758.

80200	80201	80202	80203
1	7	5	4

The inversion is done at each read or write, so if you write to address 80200, using the same field, you will retrieve the same data from address 80200.

### 1.4 Starting and stopping a Program

Starting to write an asm program looks difficult to begin with. To gain a comprehension of the RPL system, in order to avoid destroying the system data, you must first save the system data.

To start a program, all the system data must be saved somewhere. After your program has finished, it will be read back, after your program has finished, in order to restore the system data. These data are contained in the registers Ba, Da, and E.

This saving is done with the Masd instruction SAVE (or the =SAVPTR). Do it only one time, before doing any other program.

At the end of your program, you have to restore the system data with the instruction LOAD (or GOSBVL =GETPTR).

You can then exit to the RPL system with RPL (or PC=(A)).

These two instructions can be compacted into the single instruction GOVLNG =GETPTRLOOP).

The shortest program is:

```
" SAVE
% This program does nothing !
LOADRPL
@"
```

### 1.5 Working with the RPL stack

The RPL stack (the stack displayed on the screen) is stored in RAM. Each address points to an object in RAM or to an object, its address must be first read.

The stack pointer is in D1, pointing to the address of the first object. The second level, and so on. A 00000 marks the end of the stack. SAVE saves D1 (and other RPL registers) in reserved RAM. If you need to read the RPL stack, do a LOAD before, which will restore the stack pointer.

do a LOAD before exiting from your program, otherwise D1 could point to memory, that may crash your HP.

If your program needs to read the stack, it is recommended to do the argument before starting the asm code.

To read the value of a system binary on the first stack level, do the following:

```
% Reads the address of the first level in Ca
now points on the prolog of this object
do that D1 is saved in Ca
D1 points on the value of the SB
% Reads the value in Aa
stores D1
```

So, you just have to make the stack start 5 nibbles upper:

The stack starts upper, so lower levels are dropped  
Da contains the number of free 5 nibbles-blocks,  
so you shall increment it  
restored by SAVE and restored by LOAD.

After a LOAD, the old value of D1 is retrieved. In order to effectively drop an  
do LOAD D1+5 D+1. A at the end of your program (before the RPL  
do LOAD D1+5 D+1. A SAVE anywhere in your program.

To increment on the stack, you just have to create a new stack level. E.g. if the  
is in Aa:

```
sets the RPL registers
KI PNC % Tests free memory
C 1 ERREUR_C } % Insufficient mem
Adds a stack level
% Puts the object address
sets the RPL registers
```

## Instruction set

Columns in this table.

mn may be empty, or contains a M or a star. M indicates that the  
code is used (SETDEC and SETHEX). A star indicates that the carry is  
the instruction.

Column contains the instruction mnemonic.

mn indicates the fields which can be used with the instruction. f is any  
any field but A, d is a nibble value (0-15 or 1-16), x is a nibble value (0-

mn is the execution length in Saturn cycles. n is the number of nibbles in  
. If the time is not integer, take IP(time) if the instruction is on an even  
(time)+1 if the instruction is on an odd address. For tests instructions,  
times separated by a slash, the first is for a true test, the second for a  
memory instructions, the two times indicate the instruction length and  
iteration length.

from the book 'Voyage au centre de la HP48 GX' by Paul Courbis,  
1985.

*	?A#0	A	21.5/13.5
*	?A#0	a	16.5/8.5+q
*	?A#C	A	21.5/13.5
*	?A#C	a	16.5/8.5+q
*	?A<=B	A	21.5/13.5
*	?A<=B	b	16.5/8.5+q
*	?A<B	A	21.5/13.5
*	?A<B	b	16.5/8.5+q
*	?A=0	A	21.5/13.5
*	?A=0	a	16.5/8.5+q
*	?A=C	A	21.5/13.5
*	?A=C	a	16.5/8.5+q
*	?A>=B	A	21.5/13.5
*	?A>=B	b	16.5/8.5+q
*	?A>B	A	21.5/13.5
*	?A>B	b	16.5/8.5+q
*	?ABIT=0	d	20.5/12.5
*	?ABIT=1	d	20.5/12.5
*	?B#0	A	21.5/13.5
*	?B#0	a	16.5/8.5+q
*	?B#A	A	21.5/13.5
*	?B#A	a	16.5/8.5+q
*	?B<=C	A	21.5/13.5
*	?B<=C	b	16.5/8.5+q
*	?B<C	A	21.5/13.5
*	?B<C	b	16.5/8.5+q
*	?B=0	A	21.5/13.5
*	?B=0	a	16.5/8.5+q
*	?B=A	A	21.5/13.5
*	?B=A	a	16.5/8.5+q
*	?B>=C	A	21.5/13.5
*	?B>=C	b	16.5/8.5+q
*	?B>C	A	21.5/13.5
*	?B>C	b	16.5/8.5+q
*	?C#0	A	21.5/13.5
*	?C#0	a	16.5/8.5+q
*	?C#B	A	21.5/13.5
*	?C#B	a	16.5/8.5+q
*	?C#D	A	21.5/13.5
*	?C#D	a	16.5/8.5+q
*	?C<=A	A	21.5/13.5
*	?C<=A	b	16.5/8.5+q
*	?C<A	A	21.5/13.5
*	?C<A	b	16.5/8.5+q
*	?C=0	A	21.5/13.5
*	?C=0	a	16.5/8.5+q
*	?C=B	A	21.5/13.5
*	?C=B	a	16.5/8.5+q
*	?C=D	A	21.5/13.5
*	?C=D	a	16.5/8.5+q
*	?C>=A	A	21.5/13.5
*	?C>=A	b	16.5/8.5+q
*	?C>A	A	21.5/13.5
*	?C>A	b	16.5/8.5+q
*	?CBIT=0	d	20.5/12.5
*	?CBIT=1	d	20.5/12.5
*	?D#0	A	21.5/13.5
*	?D#0	a	16.5/8.5+q
*	?D<=C	A	21.5/13.5
*	?D<=C	b	16.5/8.5+q
*	?D<C	A	21.5/13.5
*	?D<C	b	16.5/8.5+q
*	?D=0	A	21.5/13.5
*	?D=0	a	16.5/8.5+q

```

?1.5/13.5
6.5/8.5+q
?1.5/13.5
6.5/8.5+q
5.5/7.5
5.5/7.5
5.5/7.5
5.5/7.5
5.5/7.5
6.5/8.5
6.5/8.5
5.5/7.5
1.5+q
}
1.5+q
}
1.5+q
}
}+q
}+q
}+q
}+q
1.5+q
}
1.5+q
}
1.5+q
}
}+q
1.5+q
}
1.5+q
}
1.5+q
}
}+q
1.5+q
}
1.5+q
}
?5,3.5
?0+p,1+q/2
9.5
9+q,1+q/2
?3.5,3.5
?0+q,1+q/2
9.5
9+q,1+q/2
1.5
1
}+q
?0.5
}+q
?0.5
}+q
?0.5
}+q
?0.5
}+q
?0.5

```

ABEX	a	4.5+q
ABEX	A	8
ABIT=0	d	7.5
ABIT=1	d	7.5
ACEX	a	4.5+q
ACEX	A	8
AD0EX		9.5
AD0XS		8.5
AD1EX		9.5
AD1XS		8.5
APCEX		19
AR0EX	f	9+q
AR0EX	W	20.5
AR1EX	f	9+q
AR1EX	W	20.5
AR2EX	f	9+q
AR2EX	W	20.5
AR3EX	f	9+q
AR3EX	W	20.5
AR4EX	f	9+q
AR4EX	W	20.5
* ASL	a	4.5+q
* ASL	A	8
ASLC		22.5
ASR	a	4.5+q
ASR	A	8
ASRB	f	8.5+q
ASRB	W	21.5
ASRC		22.5
*M B=-B	a	4.5+q
*M B=-B	A	8
*M B=-B-1	a	4.5+q
*M B=-B-1	A	8
B=0	a	4.5+q
B=0	A	8
B=A	a	4.5+q
B=A	A	8
B=B!A	f	6+q
B=B!C	f	6+q
B=B&A	f	6+q
B=B&C	f	6+q
*M B=B+1	a	4.5+q
*M B=B+1	A	8
*M B=B+A	a	4.5+q
*M B=B+A	A	8
*M B=B+B	a	4.5+q
*M B=B+B	A	8
*M B=B+C	a	4.5+q
*M B=B+C	A	8
* B=B+x+1	f	8+q
*M B=B-1	a	4.5+q
*M B=B-1	A	8
*M B=B-A	a	4.5+q
*M B=B-A	A	8
*M B=B-C	a	4.5+q
*M B=B-C	A	8
* B=B-x-1	f	8+q
B=C	a	4.5+q
B=C	A	8
*M B=C-B	a	4.5+q
*M B=C-B	A	8
BCEX	a	4.5+q
BCEX	A	8
* BSL	a	4.5+q
* BSL	A	8



C=R1	W	20.5
C=R2	f	9+q
C=R2	W	20.5
C=R3	f	9+q
C=R3	W	20.5
C=R4	f	9+q
C=R4	W	20.5
C=RSTK		9
C=ST		7
CBIT=0	d	7.5
CBIT=1	d	7.5
CD0EX		9.5
CD0XS		8.5
CD1EX		9.5
CD1XS		8.5
CDEX	a	4.5+q
CDEX	A	8
CETDEC		4
CETHEX		4
CLRHST		4.5
CLRST		7
CONFIG		13.5
CPCEX		19
CPEX	x	8
CR0EX	f	9+q
CR0EX	W	20.5
CR1EX	f	9+q
CR1EX	W	20.5
CR2EX	f	9+q
CR2EX	W	20.5
CR3EX	f	9+q
CR3EX	W	20.5
CR4EX	f	9+q
CR4EX	W	20.5
* CSL	a	4.5+q
* CSL	A	8
CSLC		22.5
CSR	a	4.5+q
CSR	A	8
CSRB	f	8.5+q
CSRB	W	21.5
CSRC		22.5
CSTEX		7
D=0	a	4.5+q
D=0	A	8
D=C	a	4.5+q
D=C	A	8
*M D=C-A	a	4.5+q
*M D=C-A	A	8
*M D=D	a	4.5+q
*M D=D	A	8
*M D=D-1	a	4.5+q
*M D=D-1	A	8
D=DIC	f	6+q
D=D&C	f	6+q
*M D=D+1	a	4.5+q
*M D=D+1	A	8
*M D=D+C	a	4.5+q
*M D=D+C	A	8
*M D=D+D	a	4.5+q
*M D=D+D	A	8
* D=D+x+1	f	8+q
*M D=D-1	a	4.5+q
*M D=D-1	A	8
*M D=D-C	a	4.5+q

}  
}+q  
}  
}  
0.5  
}.5  
}.5  
}.5  
}.5  
}.5  
}.5  
}  
}  
0.5  
}.5  
}.5  
}.5  
}.5  
}.8  
}.5  
}.9.5  
}.9+q  
}.6.5  
}.8+q  
}.9.5  
}.9.5  
}.6.5  
}.8+q  
}.9.5  
}.9+q  
}.6.5  
}.8+q  
}.9.5  
}.9.5  
}.6.5  
}.8+q  
}.1.5+q  
}  
}.2.5  
}.1.5+q  
}  
}.3.5+q  
}.2.5  
}.2.5  
}.2.5/4.5  
}.7  
}.2.5/4.5  
}.9.5  
}.5  
}.8  
}.4  
}.8.5  
}.1.5  
}  
}  
}.15+3q/2  
}.3+3q/2  
}.1.5  
}.5  
}.1.5  
}  
}  
}  
}.16.3.5

PC=(C)		26.3.5
PC=A		19
PC=C		19
R0=A	f	9+q
R0=A	W	20.5
R0=C	f	9+q
R0=C	W	20.5
R1=A	f	9+q
R1=A	W	20.5
R1=C	f	9+q
R1=C	W	20.5
R2=A	f	9+q
R2=A	W	20.5
R2=C	f	9+q
R2=C	W	20.5
R3=A	f	9+q
R3=A	W	20.5
R3=C	f	9+q
R3=C	W	20.5
R4=A	f	9+q
R4=A	W	20.5
R4=C	f	9+q
R4=C	W	20.5
RESET		7.5
RSI		8.5
RSTK=C		9
RTI		11
RTN		11
RTNC		12.5/4.5
* RTNCC		11
RTNNC		12.5/4.5
* RTNSC		11
RTNSXM		11
SB=0		4.5
SHUTDN		6.5
SR=0		4.5
SREQ?		9.5
ST=0	d	5.5
ST=1	d	5.5
ST=C		7
UNCNFG		14.5
XM=0		4.5



# Index

## —A—

Assembler, 3, 16  
Assembler syntax, 3

Masd, 3  
Masd syntax, 3

## —C—

CODE, 7  
Constants, 5

Registers, 16

## —E—

EXITs, 7  
Expressions, 6

Saturn, 16  
Saturn instructions  
SKIPs, 6  
STRING, 7  
STROBJ, 7

## —L—

Labels, 4  
Links, 4

UPs, 7